



**DESIGN**

Tufted Pile Weight:	<b>16.0 oz. per sq. yd. (542 g/m2)</b>
Product Type:	<b>Tile</b>
Construction:	<b>Tufted</b>
Minimum Sq. Yd.:	<b>No Minimum</b>
Surface Texture:	<b>Textured Patterned Loop</b>
Gauge:	<b>1/12 (47.00 rows per 10 cm)</b>
Density:	<b>8,576</b>
Weight Density:	<b>138,931</b>
Stitches Per Inch:	<b>11.2 (44.09 per 10 cm)</b>
Finished Pile Thickness:	<b>.068" (1.72 mm)</b>
Dye Method:	<b>Solution Dyed</b>
Backing Material:	<b>EcoFlex ICT</b>
Fiber Type:	<b>Colorstrand® SD Nylon</b>
Pattern Repeat:	<b>Not Applicable</b>
Size:	<b>24" x 24" (.6096 m x .6096 m)</b>
Installation Method:	<b>Quarter Turn, Brick Ashlar, Vertical Ashlar, Multi Directional</b>
Stain Release Technology:	<b>Sentry Plus Stain Protection</b>
Soil Release Technology:	<b>Sentry Soil Protection</b>
Foot Traffic Recommendation TARR:	<b>Heavy</b>

**SUSTAINABILITY**

IAQ Green Label Plus:	<b>CRI Green Label Plus GLP1098</b>
Pre-Consumer Recycled Content:	<b>48%</b>
NSF 140:	<b>EcoFlex ICT - NSF 140 Gold</b>
Declare Label:	<b>Declared</b>

**PERFORMANCE**

Static:	<b>AATCC-134 Under 3.5 KV</b>
Flammability:	<b>ASTM E 648 Class 1 (Glue Down)</b>
Smoke Density:	<b>ASTM E 662 Less than 450</b>

**SERVICE**

Warranties:	<b>Lifetime Limited Carpet Tile Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Limited Stain Warranty</b>
-------------	--



152  
Rugged Range  
Quickship Available



358  
Classic Ridge  
Quickship Available



751  
Perfect Paths  
Quickship Available



859  
Downing Stone  
Quickship Available



862  
Canyon Clay  
Quickship Available



883  
Wild Terrain  
Quickship Available



955  
Solid Ground  
Quickship Available



983  
Clean Slate  
Quickship Available



999  
Daring Drift  
Quickship Available