



DESIGN

Product Type:	Tile
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Textured Multi Colored Cut and Loop
Gauge:	1/12 (47.00 rows per 10 cm)
Density:	5,620
Weight Density:	179,840
Stitches Per Inch:	11.7 (46.06 per 10 cm)
Finished Pile Thickness:	.205" (5.21 mm)
Dye Method:	Yarn Dyed
Backing Material:	EcoFlex ICT
Fiber Type:	Ultron® Nylon
Face Weight:	32.0 oz. per sq. yd. (1085 g/m2)
Pattern Repeat:	Not Applicable
Size:	24" x 24" (.6096 m x .6096 m)
Installation Method:	QuarterTurn, BrickAshlar
Soil Release Technology:	Sentry Plus
Foot Traffic Recommendation TARR:	Severe

SUSTAINABILITY


IAQ Green Label Plus:	Green Label Plus 1098
Pre-Consumer Recycled Content:	48.00
NSF 140:	Gold
Declare Label:	Declared

PERFORMANCE

Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE


Warranties:	Lifetime Limited Carpet Tile Warranty, Lifetime Static
-------------	--




143
Highlight



158
Powder




371
Blush



577
Flawless




658
Luminous




727
Pale



858
Toned



895
Foundation



927
Shadow



964
Perfect



965
Radiant



969
Liner