



**DESIGN**

Product Type:	Woven
Construction:	Woven
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Level Patterned Cut & Loop
Density:	7,040
Weight Density:	309,760
Pitch:	270 (394 ends per meter)
Rows Per Inch:	9.4 (37.01 per 10 cm)
Finished Pile Thickness:	.225" (5.72 mm)
Dye Method:	Yarn Dyed
Backing Material:	Woven
Fiber Type:	Colorstrand® Nylon
Face Weight:	44.0 oz. per sq. yd. (1492 g/m2)
Pattern Repeat:	.25" (W) x .25" (L)
Width:	12' width (3.66 m)
Soil Release Technology:	Sentry Plus
Foot Traffic Recommendation TARR:	Severe

**SUSTAINABILITY**


IAQ Green Label Plus:	Green Label Plus 3802
NSF 140:	Gold
Declare Label:	Declared Red List Free

**PERFORMANCE**

Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

**SERVICE**


Warranties:	Lifetime Limited Woven Wear Warranty, Lifetime Static
-------------	---



00244  
Shell Stria




00245  
Sunstone



00246  
Golden Topaz



00247  
Mandarin Garnet




00249  
Tourmaline




00250  
Cleos Peridot



00251  
Tigers Eye



00252  
Pyrite



00253  
Hermatite



00254  
Champagne Diamond



00256  
Thaitian Pearl



00257  
Quartz



00258  
Smokey Citrine