



DESIGN

Product Type:	Woven
Construction:	Woven
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Level Patterned Cut & Loop
Density:	7,040
Weight Density:	309,760
Pitch:	270 (394 ends per meter)
Rows Per Inch:	9.4 (37.01 per 10 cm)
Finished Pile Thickness:	.225" (5.72 mm)
Dye Method:	Yarn Dyed
Backing Material:	Woven
Fiber Type:	Colorstrand® Nylon
Face Weight:	44.0 oz. per sq. yd. (1492 g/m2)
Pattern Repeat:	.25" (W) x .25" (L)
Width:	12' width (3.66 m)
Soil Release Technology:	Sentry Plus
Foot Traffic Recommendation TARR:	Severe

SUSTAINABILITY


IAQ Green Label Plus:	Green Label Plus 3802
NSF 140:	Gold
Declare Label:	Declared Red List Free

PERFORMANCE

Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE


Warranties:	Lifetime Limited Woven Wear Warranty, Lifetime Static
-------------	--



00244
Shell Stria




00245
Sunstone



00246
Golden Topaz




00247
Mandarin Garnet




00249
Tourmaline




00250
Cleos Peridot



00251
Tigers Eye



00252
Pyrite



00253
Hermatite



00254
Champagne Diamond



00256
Thaitian Pearl



00257
Quartz



00258
Smokey Citrine