



DESIGN

Product Type:	Woven
Construction:	Woven
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Level Patterned Cut & Loop
Density:	6,931
Weight Density:	232,189
Pitch:	216 (315 ends per meter)
Rows Per Inch:	9.5 (37.40 per 10 cm)
Finished Pile Thickness:	.174" (4.42 mm)
Dye Method:	Yarn Dyed
Backing Material:	Woven
Fiber Type:	Ultron® Nylon
Face Weight:	33.5 oz. per sq. yd. (1136 g/m2)
Pattern Repeat:	0.0" (W) x .38" (L)
Width:	12' width (3.66 m)
Soil Release Technology:	Sentry
Foot Traffic Recommendation TARR:	Heavy

SUSTAINABILITY

IAQ Green Label Plus:	CRI Green Label Plus GLP3802
NSF 140:	Woven - NSF 140 Gold
Declare Label:	Declared Red List Free

PERFORMANCE


Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE

Warranties:	Lifetime Limited Woven Wear Warranty, Lifetime Static
-------------	--



400
New Beige Rage



401
Max Flax



402
Cute Jute




403
Graphite Pyrite




404
Keen Olive Green



406
Spring Green Fling



407
Loco Mocha



408
Down Town Brown



409
Gray Highway



410
Great Slate



411
Cobalt Asphalt



412
Cool Pool



413
Wavy Navy



414
Slick Brick