



DESIGN

Product Type:	Woven
Construction:	Woven
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Level Patterned Cut & Loop
Density:	9,252
Weight Density:	254,430
Pitch:	216 (315 ends per meter)
Rows Per Inch:	7.0 (27.56 per 10 cm)
Finished Pile Thickness:	.107" (2.72 mm)
Dye Method:	Yarn Dyed
Backing Material:	Woven
Fiber Type:	Ultron® Nylon
Face Weight:	27.5 oz. per sq. yd. (932 g/m2)
Pattern Repeat:	.25" (W) x .75" (L)
Width:	12' width (3.66 m)
Soil Release Technology:	Sentry Plus
Foot Traffic Recommendation TARR:	Heavy

SUSTAINABILITY

IAQ Green Label Plus:	Green Label Plus 3802
NSF 140:	Gold
Declare Label:	Declared Red List Free

PERFORMANCE


Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE

Warranties:	Lifetime Limited Woven Wear Warranty, Lifetime Static
-------------	--



131
Captivated



152
Adoration



678
Entranced



695
Allurement



727
Enchanted



863
Spellbound



917
Wishful



929
Fascinated