



DESIGN

Woven Pile Weight:	34.0 oz. per sq. yd. (1153 g/m2)
Product Type:	Woven
Construction:	Woven
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Textured Patterned Cut and Loop
Density:	6,545
Weight Density:	222,530
Pitch:	216 (315 ends per meter)
Rows Per Inch:	9.3 (36.61 per 10 cm)
Finished Pile Thickness:	.187" (4.75 mm)
Dye Method:	Yarn Dyed
Backing Material:	Woven
Fiber Type:	Ultron® Nylon
Pattern Repeat:	.50" (W) x .50" (L)
Width:	12' width (3.66 m)
Soil Release Technology:	Sentry Plus
Foot Traffic Recommendation TARR:	Severe

SUSTAINABILITY


IAQ Green Label Plus:	CRI Green Label Plus GLP3802
NSF 140:	Woven - NSF 140 Gold
Declare Label:	Declared Red List Free

PERFORMANCE


Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE

Warranties:	Lifetime Limited Woven Wear Warranty, Lifetime Static
-------------	--



249
Grand Central
Station



314
Union Square



549
Empire State




595
The Metropolitan



649
Greenwich Village




717
Chelsea



736
Broadway



878
Brooklyn Bridge



898
Radio City



989
Rockefeller