



DESIGN

Product Type:	Broadloom
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Textured Patterned Cut and Loop
Gauge:	1/12 (49.00 rows per 10 cm)
Density:	7,714
Weight Density:	254,571
Stitches Per Inch:	12.8 (50.39 per 10 cm)
Finished Pile Thickness:	.154" (3.91 mm)
Dye Method:	Piece Dyed
Backing Material:	Unibond® Plus
Fiber Type:	Ultron® Nylon
Face Weight:	33.0 oz. per sq. yd. (1119 g/m2)
Pattern Repeat:	18" (W) x 22" (L)
Width:	12' width (3.66 m)
Soil Release Technology:	Sentry
Foot Traffic Recommendation TARR:	Heavy

SUSTAINABILITY

IAQ Green Label Plus:	Green Label Plus 3802
Pre-Consumer Recycled Content:	20%
NSF 140:	Gold
Declare Label:	Declared Red List Free

PERFORMANCE


Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE

Warranties:	Lifetime Limited Unibond® Plus Warranty, Lifetime Static
-------------	---




272
Earthen




494
Luscious



575
Cosmo




635
Poise



649
Flourish




659
Swanky



719
Plaster



729
Quartzite



739
Dust



741
Bling



846
Opulent



848
Sophisticate



852
Melt



859
Svelte



872
Polish



884
Urbane



929
Cement



948
Gravel



952
Deluxe



956
Modern



958
Mortar



969
Stone



993
Metropolitan



995
Solder