



DESIGN

| | |
|-----------------------------------|---|
| Product Type: | Broadloom |
| Construction: | Tufted |
| Minimum Sq. Yd.: | No Minimum |
| Surface Texture: | Textured Patterned Cut and Loop |
| Gauge: | 1/12 (49.00 rows per 10 cm) |
| Density: | 7,714 |
| Weight Density: | 254,571 |
| Stitches Per Inch: | 12.8 (50.39 per 10 cm) |
| Finished Pile Thickness: | .154" (3.91 mm) |
| Dye Method: | Piece Dyed |
| Backing Material: | Unibond® Plus |
| Fiber Type: | Ultron® Nylon |
| Face Weight: | 33.0 oz. per sq. yd. (1119 g/m2) |
| Pattern Repeat: | 18" (W) x 22" (L) |
| Width: | 12' width (3.66 m) |
| Soil Release Technology: | Sentry |
| Foot Traffic Recommendation TARR: | Heavy |

SUSTAINABILITY


| | |
|--------------------------------|-------------------------------------|
| IAQ Green Label Plus: | CRI Green Label Plus GLP3802 |
| Pre-Consumer Recycled Content: | 20% |
| NSF 140: | Unibond Plus - NSF 140 Gold |
| Declare Label: | Declared Red List Free |

PERFORMANCE


| | |
|----------------|---------------------------------------|
| Static: | AATCC-134 Under 3.5 KV |
| Flammability: | ASTM E 648 Class 1 (Glue Down) |
| Smoke Density: | ASTM E 662 Less than 450 |

SERVICE

| | |
|-------------|---|
| Warranties: | Lifetime Limited Unibond® Plus Warranty, Lifetime Static |
|-------------|---|



272
Earthen




494
Luscious



575
Cosmo



635
Poise



649
Flourish




659
Swanky



719
Plaster



729
Quartzite



739
Dust



741
Bling



846
Opulent



848
Sophisticate



852
Melt



859
Svelte



872
Polish



884
Urbane



929
Cement



948
Gravel



952
Deluxe



956
Modern



958
Mortar



969
Stone



993
Metropolitan



995
Solder