



DESIGN

| | |
|-----------------------------------|---|
| Woven Pile Weight: | 28.0 oz. per sq. yd. (949 g/m²) |
| Product Type: | Woven |
| Construction: | Woven |
| Minimum Sq. Yd.: | No Minimum |
| Surface Texture: | Textured Patterned Loop |
| Density: | 5,793 |
| Weight Density: | 162,204 |
| Pitch: | 216 (315 ends per meter) |
| Rows Per Inch: | 10.0 (39.37 per 10 cm) |
| Finished Pile Thickness: | .174" (4.42 mm) |
| Dye Method: | Solution Dyed |
| Backing Material: | Woven |
| Fiber Type: | Colorstrand® SD Nylon |
| Pattern Repeat: | .38" (W) x .38" (L) |
| Width: | 12' width (3.66 m) |
| Soil Release Technology: | Sentry Soil Protection |
| Foot Traffic Recommendation TARR: | Severe |

SUSTAINABILITY

| | |
|--------------------------------|-------------------------------------|
| IAQ Green Label Plus: | CRI Green Label Plus GLP3802 |
| Pre-Consumer Recycled Content: | 12% |
| NSF 140: | Woven - NSF 140 Gold |
| Declare Label: | Declared Red List Free |

PERFORMANCE


| | |
|----------------|---------------------------------------|
| Static: | AATCC-134 Under 3.5 KV |
| Flammability: | ASTM E 648 Class 1 (Glue Down) |
| Smoke Density: | ASTM E 662 Less than 450 |

SERVICE

| | |
|-------------|--|
| Warranties: | Lifetime Limited Woven Wear Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Limited Stain Warranty, Lifetime Static |
|-------------|--|



548
Design
Methodologies



838
Collaborate Form



858
Theoretical Model



899
Industrial Settings



929
Aesthetic Value



949
Material Connection



969
Product Ergonomics



998
Analytical Skills