



DESIGN

Product Type:	Woven
Construction:	Woven
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Textured Patterned Loop
Density:	5,793
Weight Density:	162,204
Pitch:	216 (315 ends per meter)
Rows Per Inch:	10.0 (39.37 per 10 cm)
Finished Pile Thickness:	.174" (4.42 mm)
Dye Method:	Solution Dyed
Backing Material:	Woven
Fiber Type:	Colorstrand® SD Nylon
Face Weight:	28.0 oz. per sq. yd. (949 g/m2)
Pattern Repeat:	.38" (W) x .38" (L)
Width:	12' width (3.66 m)
Soil Release Technology:	Sentry
Foot Traffic Recommendation TARR:	Severe

SUSTAINABILITY

IAQ Green Label Plus:	Green Label Plus 3802
Pre-Consumer Recycled Content:	12%
NSF 140:	Gold
Declare Label:	Declared Red List Free

PERFORMANCE

Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE


Warranties:	Lifetime Limited Woven Wear Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Limited Stain Warranty, Lifetime Static
-------------	--



548
Design
Methodologies



838
Collaborate Form



858
Theoretical Model



899
Industrial Settings



929
Aesthetic Value



949
Material Connection



969
Product Ergonomics



998
Analytical Skills