



**DESIGN**

Woven Pile Weight:	<b>28.0 oz. per sq. yd. (949 g/m2)</b>
Product Type:	<b>Woven</b>
Construction:	<b>Woven</b>
Minimum Sq. Yd.:	<b>No Minimum</b>
Surface Texture:	<b>Textured Patterned Loop</b>
Density:	<b>5,793</b>
Weight Density:	<b>162,204</b>
Pitch:	<b>216 (315 ends per meter)</b>
Rows Per Inch:	<b>10.0 (39.37 per 10 cm)</b>
Finished Pile Thickness:	<b>.174" (4.42 mm)</b>
Dye Method:	<b>Solution Dyed</b>
Backing Material:	<b>Woven</b>
Fiber Type:	<b>Colorstrand® SD Nylon</b>
Pattern Repeat:	<b>.38" (W) x .38" (L)</b>
Width:	<b>12' width (3.66 m)</b>
Soil Release Technology:	<b>Sentry Soil Protection</b>
Foot Traffic Recommendation TARR:	<b>Severe</b>

**SUSTAINABILITY**

IAQ Green Label Plus:	<b>CRI Green Label Plus GLP3802</b>
Pre-Consumer Recycled Content:	<b>12%</b>
NSF 140:	<b>Woven - NSF 140 Gold</b>
Declare Label:	<b>Declared Red List Free</b>

**PERFORMANCE**


Static:	<b>AATCC-134 Under 3.5 KV</b>
Flammability:	<b>ASTM E 648 Class 1 (Glue Down)</b>
Smoke Density:	<b>ASTM E 662 Less than 450</b>

**SERVICE**


Warranties:	<b>Lifetime Limited Woven Wear Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Limited Stain Warranty, Lifetime Static</b>
-------------	--



548  
Design  
Methodologies



838  
Collaborate Form



858  
Theoretical Model



899  
Industrial Settings



929  
Aesthetic Value



949  
Material Connection



969  
Product Ergonomics



998  
Analytical Skills