



DESIGN

Product Type:	Woven
Construction:	Woven
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Level Patterned Cut and Loop
Density:	8,064
Weight Density:	225,792
Pitch:	216 (315 ends per meter)
Rows Per Inch:	8.0 (31.50 per 10 cm)
Finished Pile Thickness:	.125" (3.18 mm)
Dye Method:	Solution Dyed
Backing Material:	Woven
Fiber Type:	Colorstrand® SD Nylon
Face Weight:	28.0 oz. per sq. yd. (949 g/m2)
Pattern Repeat:	1" (W) x 1.375" (L)
Width:	12' width (3.66 m)
Soil Release Technology:	Sentry Plus
Foot Traffic Recommendation TARR:	Severe

SUSTAINABILITY

IAQ Green Label Plus:	Green Label Plus 3802
Pre-Consumer Recycled Content:	12%
Post-Consumer Recycled Content:	1%
NSF 140:	Gold
Declare Label:	Declared Red List Free

PERFORMANCE

Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE

Warranties:	Lifetime Limited Woven Wear Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Limited Stain Warranty, Lifetime Static
-------------	--



148
Moccasin



721
Wood Ash



739
Chenille



851
Stone Hearth



878
Dunes



968
Smoke



969
Puritan



985
Storm



989
Carbon