



DESIGN

Product Type:	Woven
Construction:	Woven
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Level Patterned Cut and Loop
Density:	8,049
Weight Density:	221,347
Pitch:	216 (315 ends per meter)
Rows Per Inch:	8.0 (31.50 per 10 cm)
Finished Pile Thickness:	.123" (3.12 mm)
Dye Method:	Solution Dyed / Yarn Dyed
Backing Material:	Woven
Fiber Type:	Colorstrand® Nylon
Face Weight:	27.5 oz. per sq. yd. (932 g/m2)
Pattern Repeat:	4" (W) x 4" (L)
Width:	12' width (3.66 m)
Soil Release Technology:	Sentry Plus
GSA Stain Release Rating:	Pass
Foot Traffic Recommendation TARR:	Heavy

SUSTAINABILITY

IAQ Green Label Plus:	Green Label Plus 3802
NSF 140:	Gold
Declare Label:	Declared Red List Free

PERFORMANCE

Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE


Warranties:	Lifetime Limited Woven Wear Warranty, Lifetime Static
-------------	--




139
Cornsilk



718
Bone




851
Camel



859
Shadow



878
Bronze



955
Ash Grey



978
Dark Lava



989
Smokey Black