



DESIGN

| | |
|-----------------------------------|---|
| Woven Pile Weight: | 24.0 oz. per sq. yd. (814 g/m2) |
| Product Type: | Woven |
| Construction: | Woven |
| Minimum Sq. Yd.: | No Minimum |
| Surface Texture: | Level Patterned Loop |
| Density: | 6,216 |
| Weight Density: | 149,184 |
| Pitch: | 216 (315 ends per meter) |
| Rows Per Inch: | 8.0 (31.50 per 10 cm) |
| Finished Pile Thickness: | .139" (3.53 mm) |
| Dye Method: | Solution Dyed |
| Backing Material: | Woven |
| Fiber Type: | Duracolor® Premium Nylon |
| Fiber Technology: | Duracolor® by Mohawk Group's Stain Resistant System. Passes GSA requirements for permanent stain resistant carpet. |
| Pattern Repeat: | 12" (W) x 18" (L) |
| Width: | 12' width (3.66 m) |
| Soil Release Technology: | Sentry Soil Protection |
| GSA Stain Release Rating: | Pass |
| Foot Traffic Recommendation TARR: | Heavy |

SUSTAINABILITY

| | |
|---------------------------------|-------------------------------------|
| IAQ Green Label Plus: | CRI Green Label Plus GLP3802 |
| Pre-Consumer Recycled Content: | 10% |
| Post-Consumer Recycled Content: | 1% |
| NSF 140: | Woven - NSF 140 Gold |
| Declare Label: | Declared Red List Free |

PERFORMANCE

| | |
|----------------|---------------------------------------|
| Static: | AATCC-134 Under 3.5 KV |
| Flammability: | ASTM E 648 Class 1 (Glue Down) |
| Smoke Density: | ASTM E 662 Less than 450 |

SERVICE

| | |
|-------------|---|
| Warranties: | Lifetime Limited Woven Wear Warranty, Lifetime Duracolor Stain Warranty, Lifetime Static |
|-------------|---|



747
Ensemble



898
Garment



959
Wardrobe



989
Attire