



**DESIGN**

Product Type:	<b>Broadloom</b>
Construction:	<b>Tufted</b>
Minimum Sq. Yd.:	<b>No Minimum</b>
Surface Texture:	<b>Patterned Tip Shear</b>
Gauge:	<b>1/12 (47.00 rows per 10 cm)</b>
Density:	<b>7,371</b>
Weight Density:	<b>265,356</b>
Stitches Per Inch:	<b>12.0 (47.24 per 10 cm)</b>
Finished Pile Thickness:	<b>.175" (4.45 mm)</b>
Dye Method:	<b>Solution Dyed</b>
Backing Material:	<b>Unibond® Plus</b>
Fiber Type:	<b>Colorstrand® SD Nylon</b>
Face Weight:	<b>36.0 oz. per sq. yd. (1221 g/m2)</b>
Pattern Repeat:	<b>18" (W) x 36.75" (L)</b>
Width:	<b>12' width (3.66 m)</b>
Soil Release Technology:	<b>Sentry Plus</b>
Foot Traffic Recommendation TARR:	<b>Heavy</b>

**SUSTAINABILITY**

IAQ Green Label Plus:	<b>Green Label Plus 3802</b>
Pre-Consumer Recycled Content:	<b>39%</b>
NSF 140:	<b>Gold</b>
Declare Label:	<b>Declared Red List Free</b>

**PERFORMANCE**


Static:	<b>AATCC-134 Under 3.5 KV</b>
Flammability:	<b>ASTM E 648 Class 1 (Glue Down)</b>
Smoke Density:	<b>ASTM E 662 Less than 450</b>

**SERVICE**


Warranties:	<b>Lifetime Limited Unibond® Plus Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Limited Stain Warranty, Lifetime Static</b>
-------------	---



141  
Adventure



711  
Crossing



731  
Exploration




858  
Course



859  
Expedition



869  
Odyssey




889  
Passage



945  
Quest



948  
Route



965  
Trek



975  
Sojourn



989  
Journey