



DESIGN

Product Type:	Broadloom
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Patterned Tip Shear
Gauge:	1/12 (47.00 rows per 10 cm)
Density:	7,503
Weight Density:	270,108
Stitches Per Inch:	11.0 (43.31 per 10 cm)
Finished Pile Thickness:	.163" (4.14 mm)
Dye Method:	Solution Dyed
Backing Material:	Unibond® Plus
Fiber Type:	Colorstrand® SD Nylon
Face Weight:	36.0 oz. per sq. yd. (1221 g/m2)
Pattern Repeat:	18" (W) x 23.67" (L)
Width:	12' width (3.66 m)
Soil Release Technology:	Sentry Plus
Foot Traffic Recommendation TARR:	Heavy

SUSTAINABILITY


IAQ Green Label Plus:	Green Label Plus 3802
Pre-Consumer Recycled Content:	39.00
NSF 140:	Gold
Declare Label:	Declared Red List Free

PERFORMANCE


Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE


Warranties:	Lifetime Limited Unibond® Plus Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Limited Stain Warranty, Lifetime Static
-------------	---




141
Adventure




711
Crossing




731
Exploration



858
Course



859
Expedition



869
Odyssey



889
Passage



945
Quest



948
Route



965
Trek



975
Sojourn



989
Journey