



DESIGN

Product Type:	Woven
Construction:	Woven
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Level Patterned Cut & Loop
Density:	7,814
Weight Density:	218,792
Pitch:	216 (315 ends per meter)
Rows Per Inch:	8.0 (31.50 per 10 cm)
Finished Pile Thickness:	.129" (3.28 mm)
Dye Method:	Solution Dyed
Backing Material:	Woven
Fiber Type:	Colorstrand® SD Nylon
Face Weight:	28.0 oz. per sq. yd. (949 g/m2)
Pattern Repeat:	1" (W) x 1.50" (L)
Width:	12' (3.66 m)
Soil Release Technology:	Sentry Plus
Foot Traffic Recommendation TARR:	Severe

SUSTAINABILITY


IAQ Green Label Plus:	Green Label Plus 3802
Pre-Consumer Recycled Content:	12%
NSF 140:	Gold
Declare Label:	Declared Red List Free

PERFORMANCE

Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE

Warranties:	Lifetime Static, Lifetime Limited Colorfastness to Light, Lifetime Limited Woven Warranty, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Stain Warranty
-------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------



564
Blue Dacnis




585
Cobalt Parakeet



684
Green Ibis



727
Gray Nunlet



833
Geoldi Antbird



853
Brown Woodcreeper



864
Chocolate Toad



958
Gray Antwren



969
Slate Antshrike



999
Black Phoebe