



**DESIGN**

|                                   |   |
|-----------------------------------|---|
| Product Type:                     | <b>Broadloom</b>  |
| Construction:                     | <b>Tufted</b>   |
| Minimum Sq. Yd.:                  | <b>No Minimum</b>   |
| Surface Texture:                  | <b>Textured Patterned Loop</b>  |
| Gauge:                            | <b>1/12 (47.00 rows per 10 cm)</b>  |
| Density:                          | <b>7,912</b>  |
| Weight Density:                   | <b>158,240</b>  |
| Stitches Per Inch:                | <b>9.3 (36.61 per 10 cm)</b>  |
| Finished Pile Thickness:          | <b>.091" (2.31 mm)</b>  |
| Dye Method:                       | <b>Solution Dyed / Yarn Dyed</b>  |
| Backing Material:                 | <b>Unibond® Plus</b>  |
| Fiber Type:                       | <b>Duracolor® Premium Nylon</b>   |
| Fiber Technology:                 | <b>Duracolor® by Mohawk Group's Stain Resistant System. Passes GSA requirements for permanent stain resistant carpet.</b> |
| Face Weight:                      | <b>20.0 oz. per sq. yd. (678 g/m2)</b>  |
| Pattern Repeat:                   | <b>18" (W) x 39" (L)</b>  |
| Width:                            | <b>12' width (3.66 m)</b>   |
| Soil Release Technology:          | <b>Sentry Plus</b>  |
| GSA Stain Release Rating:         | <b>Pass</b>   |
| Foot Traffic Recommendation TARR: | <b>Severe</b>   |

**SUSTAINABILITY**


|                                 |                               |
|---------------------------------|-------------------------------|
| IAQ Green Label Plus:           | <b>Green Label Plus 3802</b>  |
| Pre-Consumer Recycled Content:  | <b>32%</b>                    |
| Post-Consumer Recycled Content: | <b>2%</b>                     |
| NSF 140:                        | <b>Gold</b>                   |
| Declare Label:                  | <b>Declared Red List Free</b> |

**PERFORMANCE**

|                |                                       |
|----------------|---------------------------------------|
| Static:        | <b>AATCC 134 Under 3.5 KV</b>         |
| Flammability:  | <b>ASTM E 648 Class I (Glue Down)</b> |
| Smoke Density: | <b>ASTM E 662 Less than 450</b>       |

**SERVICE**

|             |  |
|-------------|--|
| Warranties: | <b>Lifetime Limited Unibond® Plus Warranty, Lifetime Duracolor Stain Warranty, Lifetime Static</b> |
|-------------|--|



138  
Craftiness



268  
Ingenuity



566  
Flair



589  
Creativity



659  
Workmanship



678  
Expertise



728  
Vision



845  
Talent



858  
Trade



936  
Technique



988  
Mastery



989  
Skill