



DESIGN

| | |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------|
| Product Type: | Broadloom |
| Construction: | Tufted |
| Minimum Sq. Yd.: | No Minimum |
| Surface Texture: | Textured Patterned Loop |
| Gauge: | 1/12 (47.00 rows per 10 cm) |
| Density: | 7,912 |
| Weight Density: | 158,240 |
| Stitches Per Inch: | 9.3 (36.61 per 10 cm) |
| Finished Pile Thickness: | .091" (2.31 mm) |
| Dye Method: | Solution Dyed / Yarn Dyed |
| Backing Material: | Unibond® Plus |
| Fiber Type: | Duracolor® Premium Nylon |
| Fiber Technology: | Duracolor® by Mohawk Group's Stain Resistant System. Passes GSA requirements for permanent stain resistant carpet. |
| Face Weight: | 20.0 oz. per sq. yd. (678 g/m ²) |
| Pattern Repeat: | 18" (W) x 39" (L) |
| Width: | 12' width (3.66 m) |
| Soil Release Technology: | Sentry Plus |
| GSA Stain Release Rating: | Pass |
| Foot Traffic Recommendation TARR: | Severe |

SUSTAINABILITY


| | |
|---------------------------------|------------------------|
| IAQ Green Label Plus: | Green Label Plus 3802 |
| Pre-Consumer Recycled Content: | 32.00 |
| Post-Consumer Recycled Content: | 2.00 |
| NSF 140: | Gold |
| Declare Label: | Declared Red List Free |

PERFORMANCE

| | |
|----------------|--------------------------------|
| Static: | AATCC 134 Under 3.5 KV |
| Flammability: | ASTM E 648 Class I (Glue Down) |
| Smoke Density: | ASTM E 662 Less than 450 |

SERVICE

| | |
|-------------|---------------------------------------------------------------------------------------------|
| Warranties: | Lifetime Limited Unibond® Plus Warranty, Lifetime Duracolor Stain Warranty, Lifetime Static |
|-------------|---------------------------------------------------------------------------------------------|



138
Craftiness



268
Ingenuity



566
Flair



589
Creativity



659
Workmanship



678
Expertise



728
Vision



845
Talent



858
Trade



936
Technique



988
Mastery



989
Skill