



DESIGN

| | |
|-----------------------------------|---|
| Product Type: | Broadloom |
| Construction: | Tufted |
| Minimum Sq. Yd.: | No Minimum |
| Surface Texture: | Textured Patterned Cut & Loop |
| Gauge: | 1/12 (47.00 rows per 10 cm) |
| Density: | 7,646 |
| Weight Density: | 183,504 |
| Stitches Per Inch: | 10.3 (40.55 per 10 cm) |
| Finished Pile Thickness: | .113" (2.87 mm) |
| Dye Method: | Solution Dyed / Yarn Dyed |
| Backing Material: | Unibond® Plus |
| Fiber Type: | Duracolor® Premium Nylon |
| Fiber Technology: | Duracolor® by Mohawk Group's Stain Resistant System. Passes GSA requirements for permanent stain resistant carpet. |
| Face Weight: | 24.0 oz. per sq. yd. (814 g/m2) |
| Pattern Repeat: | 18" (W) x 30" (L) |
| Width: | 12' width (3.66 m) |
| Soil Release Technology: | Sentry |
| GSA Stain Release Rating: | Pass |
| Foot Traffic Recommendation TARR: | Severe |

SUSTAINABILITY


| | |
|---------------------------------|-------------------------------|
| IAQ Green Label Plus: | Green Label Plus 3802 |
| Pre-Consumer Recycled Content: | 33% |
| Post-Consumer Recycled Content: | 2% |
| NSF 140: | Gold |
| Declare Label: | Declared Red List Free |

PERFORMANCE


| | |
|----------------|---------------------------------------|
| Static: | AATCC-134 Under 3.5 KV |
| Flammability: | ASTM E 648 Class 1 (Glue Down) |
| Smoke Density: | ASTM E 662 Less than 450 |

SERVICE

| | |
|-------------|--|
| Warranties: | Lifetime Limited Unibond® Plus Warranty, Lifetime Duracolor Stain Warranty, Lifetime Static |
|-------------|--|



588
Hammer Down



848
High Gear



655
Fast Car



819
Finish Line




822
Full Throttle




846
Drag Racer



873
Road Course



879
Victory Lane



882
Racing Circuit



928
Speedway Junky



935
Free Pass



981
Checkered Flag



984
Super Rally