



**DESIGN**

Tufted Pile Weight:	<b>17.0 oz. per sq. yd. (576 g/m2)</b>
Product Type:	<b>Tile</b>
Construction:	<b>Tufted</b>
Minimum Sq. Yd.:	<b>No Minimum</b>
Surface Texture:	<b>Textured Multi Colored Loop</b>
Gauge:	<b>1/12 (47.00 rows per 10 cm)</b>
Density:	<b>7,286</b>
Weight Density:	<b>123,862</b>
Stitches Per Inch:	<b>9.8 per inch (38.58/10 cm)</b>
Finished Pile Thickness:	<b>.084" (2.13 mm)</b>
Dye Method:	<b>Solution Dyed / Yarn Dyed</b>
Backing Material:	<b>EcoFlex ICT</b>
Fiber Type:	<b>Antron® Legacy Nylon</b>
Fiber Technology:	<b>Duracolor® Stain Resistant System by Mohawk Group. Passes GSA requirements for permanent stain resistant carpet</b>
Pattern Repeat:	<b>Not Applicable</b>
Size:	<b>24" x 24" (.6096 m x .6096 m)</b>
Installation Method:	<b>BrickAshlar, Monolithic</b>
Soil Release Technology:	<b>DuraTech®</b>
GSA Stain Release Rating:	<b>Pass</b>
Foot Traffic Recommendation TARR:	<b>Severe</b>



214  
Outstanding



218  
Expert



228  
Prominent



311  
Phenomenal




312  
Brilliant



317  
Savvy



322  
Clever



324  
Striking



327  
Brainy

**SUSTAINABILITY**

IAQ Green Label Plus:	<b>CRI Green Label Plus GLP1098</b>
Pre-Consumer Recycled Content:	<b>42%</b>
NSF 140:	<b>EcoFlex ICT - NSF 140 Gold</b>
Declare Label:	<b>Declared</b>

**PERFORMANCE**

Static:	<b>AATCC 134 Under 3.5 KV</b>
Flammability:	<b>Passes DOC-FF-1-70 Pill Test</b>
Smoke Density:	<b>NBS Smoke Chamber NFPA-258 - Less than 450 Flaming Mode</b>

**SERVICE**

Warranties:	<b>Lifetime Limited Carpet Tile Warranty, Lifetime Static</b>
-------------	---



337  
Ingenious



418  
Distinctive



421  
Hotshot