



DESIGN

Product Type:	Tile
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Textured Multi Colored Loop
Gauge:	1/12 (47.00 rows per 10 cm)
Density:	7,286
Weight Density:	123,862
Stitches Per Inch:	9.8 per inch (38.58/10 cm)
Finished Pile Thickness:	.084" (2.13 mm)
Dye Method:	Solution Dyed / Yarn Dyed
Backing Material:	EcoFlex ICT
Fiber Type:	Antron® Legacy Nylon
Fiber Technology:	Duracolor® Stain Resistant System by Mohawk Group. Passes GSA requirements for permanent stain resistant carpet
Face Weight:	17.0 oz. per sq. yd. (576 g/m2)
Pattern Repeat:	Not Applicable
Size:	24" x 24" (.6096 m x .6096 m)
Installation Method:	BrickAshlar, Monolithic
Soil Release Technology:	DuraTech®
GSA Stain Release Rating:	Pass
Foot Traffic Recommendation TARR:	Severe

SUSTAINABILITY

IAQ Green Label Plus:	Green Label Plus 1098
Pre-Consumer Recycled Content:	42%
NSF 140:	Gold
Declare Label:	Declared

PERFORMANCE

Static:	AATCC 134 Under 3.5 KV
Flammability:	Passes DOC-FF-1-70 Pill Test
Smoke Density:	NBS Smoke Chamber NFPA-258 - Less than 450 Flaming Mode

SERVICE

Warranties:	Lifetime Limited Carpet Tile Warranty, Lifetime Static
-------------	--------------------------------------------------------



214
Outstanding



218
Expert



228
Prominent



311
Phenomenal




312
Brilliant



317
Savvy



322
Clever



324
Striking



327
Brainy



337
Ingenious



418
Distinctive



421
Hotshot