



**DESIGN**

Tufted Pile Weight:	20.0 oz. per sq. yd. (678 g/m <sup>2</sup> )
Product Type:	Tile
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Level Multi Colored Patterned Loop
Gauge:	1/12 (47.00 rows per 10 cm)
Density:	4,675
Weight Density:	93,500
Stitches Per Inch:	11.5 (45.28 per 10 cm)
Finished Pile Thickness:	.154" (3.91 mm)
Dye Method:	Solution Dyed / Yarn Dyed
Backing Material:	EcoFlex ICT
Fiber Type:	Antron® Legacy Nylon
Fiber Technology:	Duracolor® Stain Resistant System by Mohawk Group. Passes GSA requirements for permanent stain resistant carpet
Pattern Repeat:	Not Applicable
Size:	24" x 24" (.6096 m x .6096 m)
Installation Method:	Monolithic, VerticalAshlar, BrickAshlar, QuarterTurn
Soil Release Technology:	DuraTech®
GSA Stain Release Rating:	Pass
Foot Traffic Recommendation TARR:	Severe

**SUSTAINABILITY**

IAQ Green Label Plus:	CRI Green Label Plus GLP1098
Pre-Consumer Recycled Content:	41%
NSF 140:	EcoFlex ICT - NSF 140 Gold
Declare Label:	Declared

**PERFORMANCE**

Static:	AATCC 134 Under 3.5 KV
Flammability:	Passes DOC-FF-1-70 Pill Test
Smoke Density:	NBS Smoke Chamber NFPA-258 - Less than 450 Flaming Mode

**SERVICE**

Warranties:	Lifetime Limited Carpet Tile Warranty, Lifetime Static
-------------	--



114  
Organic Moire




116  
Antiquity



138  
Remnants



201  
Alluring Origins



217  
Lasting Impression



218  
Foundation



224  
Contemporary History



231  
Industrial Patina



236  
Traces



334  
Vestiges



344  
Natural Perfection



346  
Artifact



356  
Relics



512  
Rubble



537  
Cherished Ruins



548  
Preserved