




DESIGN

Product Type:	Tile
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Textured Patterned Loop
Gauge:	1/12 (47.00 rows per 10 cm)
Density:	6,315
Weight Density:	126,315
Stitches Per Inch:	9.4 (37.01 per 10 cm)
Finished Pile Thickness:	.114" (2.90 mm)
Dye Method:	Solution Dyed / Yarn Dyed
Backing Material:	EcoFlex ICT
Fiber Type:	Antron® Legacy Nylon
Fiber Technology:	Duracolor® Stain Resistant System by Mohawk Group. Passes GSA requirements for permanent stain resistant carpet
Face Weight:	20 oz. per sq. yd. (678.2 g/m2)
Pattern Repeat:	Not Applicable
Size:	24" x 24" (.6096 m x .6096 m)
Installation Method:	Monolithic, VerticalAshlar, BrickAshlar, QuarterTurn, MultiDirectional
Soil Release Technology:	DuraTech®, Permanent, Built into Fiber
GSA Stain Release Rating:	Pass
Foot Traffic Recommendation TARR:	Severe



114
Organic Moire




116
Antiquity




138
Remnants



201
Alluring Origins



217
Lasting Impression



218
Foundation



224
Contemporary History



231
Industrial Patina



236
Traces

SUSTAINABILITY

IAQ Green Label Plus:	Green Label Plus 1098
Pre-Consumer Recycled Content:	41%
NSF 140:	Gold
Declare Label:	Declared

PERFORMANCE

Static:	AATCC 134 Under 3.5 KV
Flammability:	Passes DOC-FF-1-70 Pill Test
Smoke Density:	ASTM E 662 Less than 450

SERVICE

Warranties:	Lifetime Limited Carpet Tile Warranty, Lifetime Duracolor Stain Warranty, Lifetime Static
-------------	---



334
Vestiges



344
Natural Perfection



346
Artifact



356
Relics



512
Rubble



537
Cherished Ruins



548
Preserved