



**DESIGN**

Product Type:	Tile
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Textured Multi Colored Loop
Gauge:	1/12 (47.00 rows per 10 cm)
Density:	6,102
Weight Density:	122,040
Stitches Per Inch:	9.8 (38.58 per 10 cm)
Finished Pile Thickness:	.118" (3.00 mm)
Dye Method:	Solution Dyed / Yarn Dyed
Backing Material:	EcoFlex ICT
Fiber Type:	Antron® Legacy Nylon
Fiber Technology:	Duracolor® Stain Resistant System by Mohawk Group. Passes GSA requirements for permanent stain resistant carpet
Face Weight:	20 oz. per sq. yd. (678.2 g/m <sup>2</sup> )
Pattern Repeat:	Not Applicable
Size:	24" x 24" (.6096 m x .6096 m)
Installation Method:	Monolithic, VerticalAshlar, BrickAshlar, QuarterTurn, MultiDirectional
Soil Release Technology:	DuraTech®
GSA Stain Release Rating:	Pass
Foot Traffic Recommendation TARR:	Severe

**SUSTAINABILITY**


IAQ Green Label Plus:	Green Label Plus 1098
Pre-Consumer Recycled Content:	41%
NSF 140:	Gold
Declare Label:	Declared

**PERFORMANCE**


Static:	AATCC 134 Under 3.5 KV
Flammability:	Passes DOC-FF-1-70 Pill Test
Smoke Density:	NBS Smoke Chamber NFPA-258 - Less than 450 Flaming Mode

**SERVICE**


Warranties:	Lifetime Limited Carpet Tile Warranty, Lifetime Static
-------------	--



214  
Outstanding



218  
Expert



228  
Prominent



311  
Phenomenal




312  
Brilliant




317  
Savvy



322  
Clever



324  
Striking



327  
Brainy



337  
Ingenious



418  
Distinctive



421  
Hotshot