



DESIGN

Product Type:	Tile
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Textured Patterned Loop
Gauge:	1/12 (47.00 rows per 10 cm)
Density:	8,526
Weight Density:	153,468
Stitches Per Inch:	9.8 (38.58 per 10 cm)
Finished Pile Thickness:	.076" (1.93 mm)
Dye Method:	Yarn Dyed
Backing Material:	EcoFlex ICT
Fiber Type:	Antron® Legacy Nylon
Fiber Technology:	Duracolor® Stain Resistant System by Mohawk Group. Passes GSA requirements for permanent stain resistant carpet
Face Weight:	18.0 oz. per sq. yd. (610 g/m2)
Pattern Repeat:	Not Applicable
Size:	24" x 24" (.6096 m x .6096 m)
Installation Method:	Monolithic, BrickAshlar, QuarterTurn, VerticalAshlar
Soil Release Technology:	DuraTech®, Permanent, Built into Fiber
GSA Stain Release Rating:	Pass
Foot Traffic Recommendation TARR:	Severe

SUSTAINABILITY

IAQ Green Label Plus:	Green Label Plus 1098
Pre-Consumer Recycled Content:	40.00
NSF 140:	Gold
Declare Label:	Declared

PERFORMANCE


Static:	AATCC 134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE


Warranties:	Lifetime Limited Carpet Tile Warranty, Lifetime Duracolor Stain Warranty, Lifetime Static
-------------	---



104 Chamois




201 Green Tint




226 Wheatland




228 Castle Grey




328 Flint Stone



331 Everglades



344 Briar



346 Mayfair Beige



354 Beach Tan



357
Shadow Blue



406
Burnished Gold



507
Persian Blue



512
Rustic



534
Sable



538
Smoked Khol



808
Mystified