




DESIGN

Tufted Pile Weight:	16.0 oz. per sq. yd. (542 g/m ²)
Product Type:	Tile
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Level Patterned Loop
Gauge:	1/10 (39.37 rows per 10 cm)
Density:	6,329
Weight Density:	101,274
Stitches Per Inch:	9.1 (35.83 per 10 cm)
Finished Pile Thickness:	.091" (2.31 mm)
Dye Method:	Solution Dyed
Backing Material:	EcoFlex NXT
Fiber Type:	Duracolor® Premium Nylon
Fiber Technology:	Duracolor® by Mohawk Group's Stain Resistant System. Passes GSA requirements for permanent stain resistant carpet.
Pattern Repeat:	Not Applicable
Size:	24" x 24" (.6096 m x .6096 m)
Installation Method:	BrickAshlar
Soil Release Technology:	Sentry Soil Protection
GSA Stain Release Rating:	Pass
Foot Traffic Recommendation TARR:	Severe



137
Cognate



585
Interaction



589
Correlate




647
Companion




727
Pendant



851
Counterpart



873
Parallel



876
Correspondent



879
Interchange

SUSTAINABILITY

IAQ Green Label Plus:	CRI Green Label Plus GLP1171
Pre-Consumer Recycled Content:	57%
Post-Consumer Recycled Content:	1%
NSF 140:	EcoFlex NXT - NSF 140 Gold
Declare Label:	Declared Red List Free

PERFORMANCE

Static:	AATCC 134 Under 3.5 KV
Flammability:	Passes DOC-FF-1-70 Pill Test
Smoke Density:	NBS Smoke Chamber NFPA-258 - Less than 450 Flaming Mode

SERVICE

Warranties:	Lifetime Limited Carpet Tile Warranty, Lifetime Duracolor Stain Warranty, Lifetime Static
-------------	---



937
Complement



959
Mate



965
Reciprocity