



**DESIGN**

---

Product Type:	Tile
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Textured Patterned Loop
Gauge:	1/12 (47.00 rows per 10 cm)
Density:	5,806
Weight Density:	116,129
Stitches Per Inch:	10.0 (39.37 per 10 cm)
Finished Pile Thickness:	.124" (3.15 mm)
Dye Method:	Solution Dyed / Yarn Dyed
Backing Material:	EcoFlex NXT
Fiber Type:	Duracolor® Premium Nylon
Fiber Technology:	Duracolor® by Mohawk Group's Stain Resistant System. Passes GSA requirements for permanent stain resistant carpet.
Face Weight:	20.0 oz. per sq. yd. (678 g/m <sup>2</sup> )
Pattern Repeat:	Not Applicable
Size:	24" x 24" (.6096 m x .6096 m)
Installation Method:	QuarterTurn, Monolithic, VerticalAshlar, BrickAshlar
Soil Release Technology:	Sentry Soil Protection
GSA Stain Release Rating:	Pass
Foot Traffic Recommendation TARR:	Severe

**SUSTAINABILITY**

---

IAQ Green Label Plus:	Green Label Plus 1171
Pre-Consumer Recycled Content:	56%
Post-Consumer Recycled Content:	1%
NSF 140:	Gold
Declare Label:	Declared Red List Free

**PERFORMANCE**


---

Static:	AATCC 134 Under 3.5 KV
Flammability:	ASTM E 648 Class I (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

**SERVICE**

---


Warranties:	Lifetime Limited Carpet Tile Warranty, Lifetime Duracolor Stain Warranty, Lifetime Static
-------------	---



138  
Craftiness



268  
Ingenuity




566  
Flair



589  
Creativity




659  
Workmanship



678  
Expertise



728  
Vision



845  
Talent



858  
Trade



936  
Technique



988  
Mastery



989  
Skill