



DESIGN


Product Type:	Tile
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Level Multi Colored Loop
Gauge:	1/10 (39.37 rows per 10 cm)
Density:	5,828
Weight Density:	99,085
Stitches Per Inch:	8.5 (33.46 per 10 cm)
Finished Pile Thickness:	.105" (2.67 mm)
Dye Method:	Solution Dyed / Yarn Dyed
Backing Material:	EcoFlex NXT
Fiber Type:	Duracolor® Premium Nylon
Fiber Technology:	Duracolor® by Mohawk Group's Stain Resistant System. Passes GSA requirements for permanent stain resistant carpet.
Face Weight:	17.0 oz. per sq. yd. (576 g/m2)
Pattern Repeat:	Not Applicable
Size:	24" x 24" (.6096 m x .6096 m)
Installation Method:	Monolithic
Soil Release Technology:	Sentry Soil Protection
GSA Stain Release Rating:	Pass
Foot Traffic Recommendation TARR:	Severe



214
Sandy Shore




218
Hammered Tin



228
Natural Hybrid



311
Chameleon Foil



312
Enriched Garnet




317
Velvet Underground



322
Sundried Tomato



324
Grounded Earth



327
Twilight Format

SUSTAINABILITY

IAQ Green Label Plus:	CRI Green Label Plus GLP1171
Pre-Consumer Recycled Content:	58%
Post-Consumer Recycled Content:	1%
NSF 140:	EcoFlex NXT - NSF 140 Gold
Declare Label:	Declared Red List Free

PERFORMANCE

Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE

Warranties:	Lifetime Limited Carpet Tile Warranty, Lifetime Duracolor Stain Warranty, Lifetime Static
-------------	---



337
Slatened Sky



418
Burnished Iron



421
Metal Works