



DESIGN

| | |
|-----------------------------------|--|
| Product Type: | Tile |
| Construction: | Tufted |
| Minimum Sq. Yd.: | No Minimum |
| Surface Texture: | Level Multi Colored Loop |
| Gauge: | 1/10 (39.37 rows per 10 cm) |
| Density: | 6,117 |
| Weight Density: | 159,058 |
| Stitches Per Inch: | 11.5 per inch (45.28 per 10 cm) |
| Finished Pile Thickness: | .153" (3.89 mm) |
| Dye Method: | Solution Dyed / Yarn Dyed |
| Backing Material: | EcoFlex NXT |
| Fiber Type: | Duracolor® Premium Nylon |
| Fiber Technology: | Duracolor® by Mohawk Group's Stain Resistant System. Passes GSA requirements for permanent stain resistant carpet. |
| Face Weight: | 26.0 oz per sq. yd. (882 g/m2) |
| Pattern Repeat: | Not Applicable |
| Size: | 24" x 24" (.6096 m x .6096 m) |
| Installation Method: | Monolithic |
| Soil Release Technology: | Sentry Plus |
| GSA Stain Release Rating: | Pass |
| Foot Traffic Recommendation TARR: | Severe |

SUSTAINABILITY


| | |
|---------------------------------|------------------------|
| IAQ Green Label Plus: | Green Label Plus 1171 |
| Pre-Consumer Recycled Content: | 54% |
| Post-Consumer Recycled Content: | 1% |
| NSF 140: | Gold |
| Declare Label: | Declared Red List Free |

PERFORMANCE

| | |
|----------------|--------------------------------|
| Static: | AATCC-134 Under 3.5 KV |
| Flammability: | ASTM E 648 Class 1 (Glue Down) |
| Smoke Density: | ASTM E 662 Less than 450 |

SERVICE


| | |
|-------------|---|
| Warranties: | Lifetime Limited Carpet Tile Warranty, Lifetime Duracolor Stain Warranty, Lifetime Static |
|-------------|---|



214
Sandy Shore



218
Hammered Tin



228
Natural Hybrid



311
Chameleon Foil



312
Enriched Garnet



317
Velvet Underground



322
Sundried Tomato



324
Grounded Earth



327
Twilight Format



337
Slatened Sky



418
Burnished Iron



421
Metal Works