



DESIGN

Product Type:	Tile
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Textured Patterned Loop
Gauge:	1/12 (47.00 rows per 10 cm)
Density:	6,336
Weight Density:	139,392
Stitches Per Inch:	10.8 (42.52 per 10 cm)
Finished Pile Thickness:	.125" (3.18 mm)
Dye Method:	Solution Dyed / Yarn Dyed
Backing Material:	EcoFlex NXT
Fiber Type:	Duracolor® Premium Nylon
Fiber Technology:	Duracolor® by Mohawk Group's Stain Resistant System. Passes GSA requirements for permanent stain resistant carpet.
Face Weight:	22.0 oz. per sq. yd. (746 g/m2)
Pattern Repeat:	Not Applicable
Size:	24" x 24" (.6096 m x .6096 m)
Installation Method:	QuarterTurn
Soil Release Technology:	Sentry Soil Protection
GSA Stain Release Rating:	Pass
Foot Traffic Recommendation TARR:	Severe

SUSTAINABILITY

IAQ Green Label Plus:	Green Label Plus 1171
Pre-Consumer Recycled Content:	56%
Post-Consumer Recycled Content:	1%
NSF 140:	Gold
Declare Label:	Declared Red List Free

PERFORMANCE

Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE

Warranties:	Lifetime Limited Carpet Tile Warranty, Lifetime Duracolor Stain Warranty, Lifetime Static
-------------	---



588
Hammer Down



848
High Gear




655
Fast Car




819
Finish Line




822
Full Throttle




846
Drag Racer



873
Road Course



879
Victory Lane



882
Racing Circuit



928
Speedway Junky



935
Free Pass



981
Checkered Flag



984
Super Rally