



### DESIGN

Tufted Pile Weight:	<b>18.0 oz. per sq. yd. (610 g/m2)</b>
Product Type:	<b>Tile</b>
Construction:	<b>Tufted</b>
Minimum Sq. Yd.:	<b>No Minimum</b>
Surface Texture:	<b>Textured Patterned Loop</b>
Gauge:	<b>1/10 (39.37 rows per 10 cm)</b>
Density:	<b>5,445</b>
Weight Density:	<b>98,016</b>
Stitches Per Inch:	<b>11.1 per inch (43.70 per 10 cm)</b>
Finished Pile Thickness:	<b>.119" (3.02 mm)</b>
Dye Method:	<b>Solution Dyed / Yarn Dyed</b>
Backing Material:	<b>EcoFlex NXT</b>
Fiber Type:	<b>Duracolor® Premium Nylon</b>
Fiber Technology:	<b>Duracolor® by Mohawk Group's Stain Resistant System. Passes GSA requirements for permanent stain resistant carpet.</b>
Pattern Repeat:	<b>Not Applicable</b>
Size:	<b>24" x 24" (.6096 m x .6096 m)</b>
Installation Method:	<b>QuarterTurn, BrickAshlar, VerticalAshlar</b>
Soil Release Technology:	<b>Sentry Soil Protection</b>
Foot Traffic Recommendation TARR:	<b>Severe</b>

### SUSTAINABILITY

IAQ Green Label Plus:	<b>CRI Green Label Plus GLP1171</b>
Pre-Consumer Recycled Content:	<b>56%</b>
Post-Consumer Recycled Content:	<b>1%</b>
NSF 140:	<b>EcoFlex NXT - NSF 140 Gold</b>
Declare Label:	<b>Declared Red List Free</b>

### PERFORMANCE

Static:	<b>AATCC-134 Under 3.5 KV</b>
Flammability:	<b>ASTM E 648 Class 1 (Glue Down)</b>
Smoke Density:	<b>ASTM E 662 Less than 450</b>

### SERVICE

Warranties:	<b>Lifetime Limited Carpet Tile Warranty, Lifetime Duracolor Stain Warranty, Lifetime Static</b>
-------------	--




131  
Argyle




278  
Herringbone




529  
Chambray




585  
Denim




641  
Houndstooth




676  
Chino



695  
Sharkskin



718  
Tweed



851  
Plaid



859  
Pinstripe



894  
Twill



976  
Corduroy