



**DESIGN**

Product Type:	Tile
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Textured Patterned Loop
Gauge:	1/10 (39.37 rows per 10 cm)
Density:	5,445
Weight Density:	98,016
Stitches Per Inch:	11.1 per inch (43.70 per 10 cm)
Finished Pile Thickness:	.119" (3.02 mm)
Dye Method:	Solution Dyed / Yarn Dyed
Backing Material:	EcoFlex NXT
Fiber Type:	Duracolor® Premium Nylon
Fiber Technology:	Duracolor® by Mohawk Group's Stain Resistant System. Passes GSA requirements for permanent stain resistant carpet.
Face Weight:	18.0 oz. per sq. yd. (610 g/m2)
Pattern Repeat:	Not Applicable
Size:	24" x 24" (.6096 m x .6096 m)
Installation Method:	QuarterTurn, BrickAshlar, VerticalAshlar
Soil Release Technology:	Sentry Soil Protection
Foot Traffic Recommendation TARR:	Severe

**SUSTAINABILITY**


IAQ Green Label Plus:	Green Label Plus 1171
Pre-Consumer Recycled Content:	56.00
Post-Consumer Recycled Content:	1.00
NSF 140:	Gold
Declare Label:	Declared Red List Free

**PERFORMANCE**

Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

**SERVICE**

Warranties:	Lifetime Limited Carpet Tile Warranty, Lifetime Duracolor Stain Warranty, Lifetime Static
-------------	---




894  
Twill



851  
Plaid



859  
Pinstripe




131  
Argyle



676  
Chino




529  
Chambray



585  
Denim



976  
Corduroy



695  
Sharkskin



278  
Herringbone



641  
Houndstooth



718  
Tweed