



### DESIGN

|                                   |  |
|-----------------------------------|--|
| Product Type:                     | Tile   |
| Construction:                     | Tufted   |
| Minimum Sq. Yd.:                  | No Minimum   |
| Surface Texture:                  | Textured Patterned Cut and Loop  |
| Gauge:                            | 1/10 (39.37 rows per 10 cm)  |
| Density:                          | 7,411  |
| Weight Density:                   | 155,647  |
| Stitches Per Inch:                | 10.5 per inch (41.34 per 10 cm)  |
| Finished Pile Thickness:          | .102" (2.59 mm)  |
| Dye Method:                       | Solution Dyed / Yarn Dyed  |
| Backing Material:                 | EcoFlex NXT  |
| Fiber Type:                       | Duracolor® Premium Nylon   |
| Fiber Technology:                 | Duracolor® by Mohawk Group's Stain Resistant System. Passes GSA requirements for permanent stain resistant carpet. |
| Face Weight:                      | 21.0 oz. per sq. yd. (712 g/m2)  |
| Pattern Repeat:                   | Not Applicable   |
| Size:                             | 24" x 24" (.6096 m x .6096 m)  |
| Installation Method:              | QuarterTurn, BrickAshlar, VerticalAshlar   |
| Soil Release Technology:          | Sentry Soil Protection   |
| Foot Traffic Recommendation TARR: | Severe   |

### SUSTAINABILITY

|                                 |                              |
|---------------------------------|------------------------------|
| IAQ Green Label Plus:           | CRI Green Label Plus GLP1171 |
| Pre-Consumer Recycled Content:  | 45%                          |
| Post-Consumer Recycled Content: | 1%                           |
| NSF 140:                        | EcoFlex NXT - NSF 140 Gold   |
| Declare Label:                  | Declared                     |

### PERFORMANCE


|                |                                |
|----------------|--------------------------------|
| Static:        | AATCC-134 Under 3.5 KV         |
| Flammability:  | ASTM E 648 Class 1 (Glue Down) |
| Smoke Density: | ASTM E 662 Less than 450       |

### SERVICE

|             |   |
|-------------|---|
| Warranties: | Lifetime Limited Carpet Tile Warranty, Lifetime Duracolor Stain Warranty, Lifetime Static |
|-------------|---|



894  
Twill




851  
Plaid



859  
Pinstripe



131  
Argyle



676  
Chino




529  
Chambray




585  
Denim



976  
Corduroy



695  
Sharkskin



278  
Herringbone



641  
Houndstooth



718  
Tweed