



DESIGN

| | |
|-----------------------------------|--|
| Tufted Pile Weight: | 21.0 oz. per sq. yd. (712 g/m ²) |
| Product Type: | Tile |
| Construction: | Tufted |
| Minimum Sq. Yd.: | No Minimum |
| Surface Texture: | Textured Patterned Cut and Loop |
| Gauge: | 1/10 (39.37 rows per 10 cm) |
| Density: | 7,411 |
| Weight Density: | 155,647 |
| Stitches Per Inch: | 10.5 per inch (41.34 per 10 cm) |
| Finished Pile Thickness: | .102" (2.59 mm) |
| Dye Method: | Solution Dyed / Yarn Dyed |
| Backing Material: | EcoFlex NXT |
| Fiber Type: | Duracolor® Premium Nylon |
| Fiber Technology: | Duracolor® by Mohawk Group's Stain Resistant System. Passes GSA requirements for permanent stain resistant carpet. |
| Pattern Repeat: | Not Applicable |
| Size: | 24" x 24" (.6096 m x .6096 m) |
| Installation Method: | QuarterTurn, BrickAshlar, VerticalAshlar |
| Soil Release Technology: | Sentry Soil Protection |
| Foot Traffic Recommendation TARR: | Severe |

SUSTAINABILITY

| | |
|---------------------------------|------------------------------|
| IAQ Green Label Plus: | CRI Green Label Plus GLP1171 |
| Pre-Consumer Recycled Content: | 45% |
| Post-Consumer Recycled Content: | 1% |
| NSF 140: | EcoFlex NXT - NSF 140 Gold |
| Declare Label: | Declared |

PERFORMANCE

| | |
|----------------|--------------------------------|
| Static: | AATCC-134 Under 3.5 KV |
| Flammability: | ASTM E 648 Class 1 (Glue Down) |
| Smoke Density: | ASTM E 662 Less than 450 |

SERVICE

| | |
|-------------|---|
| Warranties: | Lifetime Limited Carpet Tile Warranty, Lifetime Duracolor Stain Warranty, Lifetime Static |
|-------------|---|



131
Argyle



278
Herringbone




529
Chambray




585
Denim




641
Houndstooth




676
Chino



695
Sharkskin



718
Tweed



851
Plaid



859
Pinstripe



894
Twill



976
Corduroy