



DESIGN

Tufted Pile Weight:	21.0 oz. per sq. yd. (712 g/m ²)
Product Type:	Tile
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Textured Patterned Cut & Loop
Gauge:	1/10 (39.37 rows per 10 cm)
Density:	7,411
Weight Density:	155,647
Stitches Per Inch:	10.5 per inch (41.34 per 10 cm)
Finished Pile Thickness:	.102" (2.59 mm)
Dye Method:	Solution Dyed / Yarn Dyed
Backing Material:	EcoFlex NXT
Fiber Type:	Duracolor® Premium Nylon
Fiber Technology:	Duracolor® by Mohawk Group's Stain Resistant System. Passes GSA requirements for permanent stain resistant carpet.
Pattern Repeat:	Not Applicable
Size:	24" x 24" (.6096 m x .6096 m)
Installation Method:	Quarter Turn, Brick Ashlar, Vertical Ashlar
GSA Stain Release Rating:	Pass
Stain Release Technology:	Permanent, Built into Fiber
Soil Release Technology:	Sentry Soil Protection
Foot Traffic Recommendation TARR:	Severe

SUSTAINABILITY

IAQ Green Label Plus:	CRI Green Label Plus GLP1171
Pre-Consumer Recycled Content:	45%
NSF 140:	EcoFlex NXT - NSF 140 Gold
Declare Label:	Declared

PERFORMANCE

Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE

Warranties:	Lifetime Limited Carpet Tile Warranty, Lifetime Duracolor Stain Warranty, Lifetime Static
-------------	---



131
Argyle




278
Herringbone




529
Chambray




585
Denim




641
Houndstooth




676
Chino



695
Sharkskin



718
Tweed



851
Plaid



859
Pinstripe



894
Twill



976
Corduroy