



DESIGN

| | |
|-----------------------------------|---|
| Tufted Pile Weight: | 19.0 oz. per sq. yd. (644 g/m2) |
| Product Type: | Tile |
| Construction: | Tufted |
| Minimum Sq. Yd.: | No Minimum |
| Surface Texture: | Textured Patterned Loop |
| Gauge: | 1/12 (47.00 rows per 10 cm) |
| Density: | 7,355 |
| Weight Density: | 139,745 |
| Stitches Per Inch: | 10.6 (47.73 per 10 cm) |
| Finished Pile Thickness: | .093" (2.36 mm) |
| Dye Method: | Solution Dyed |
| Backing Material: | EcoFlex ICT |
| Fiber Type: | Antron® Lumena™ Nylon |
| Pattern Repeat: | Not Applicable |
| Size: | 24" x 24" (.6096 m x .6096 m) |
| Installation Method: | Monolithic, Vertical Ashlar, Brick Ashlar, Quarter Turn, Multi Directional |
| GSA Stain Release Rating: | Pass |
| Soil Release Technology: | DuraTech® |
| Foot Traffic Recommendation TARR: | Severe |

SUSTAINABILITY

| | |
|--------------------------------|-------------------------------------|
| IAQ Green Label Plus: | CRI Green Label Plus GLP1098 |
| Pre-Consumer Recycled Content: | 41% |
| NSF 140: | EcoFlex ICT - NSF 140 Gold |
| Declare Label: | Declared |

PERFORMANCE

| | |
|----------------|---------------------------------------|
| Static: | AATCC-134 Under 3.5 KV |
| Flammability: | ASTM E 648 Class 1 (Glue Down) |
| Smoke Density: | ASTM E 662 Less than 450 |

SERVICE

| | |
|-------------|---|
| Warranties: | Lifetime Limited Carpet Tile Warranty, Lifetime Static |
|-------------|---|



727
Transform



739
Convert



847
Reshape



859
Adjust



868
Fixed



947
Complex



969
Reform



979
Modify



988
Adapt