



DESIGN

Tufted Pile Weight:	23.0 oz. per sq. yd. (780 g/m2)
Product Type:	Tile
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Textured Patterned Loop
Gauge:	1/12 (47.00 rows per 10 cm)
Density:	6,225
Weight Density:	143,187
Stitches Per Inch:	11.3 (44.49 per 10 cm)
Finished Pile Thickness:	.133" (3.38 mm)
Dye Method:	Solution Dyed / Yarn Dyed
Backing Material:	EcoFlex NXT
Fiber Type:	Duracolor® Premium Nylon
Fiber Technology:	Duracolor® by Mohawk Group's Stain Resistant System. Passes GSA requirements for permanent stain resistant carpet.
Pattern Repeat:	Not Applicable
Size:	24" x 24" (.6096 m x .6096 m)
Installation Method:	Quarter Turn, Vertical Ashlar, Brick Ashlar
GSA Stain Release Rating:	Pass
Stain Release Technology:	Permanent, Built into Fiber
Soil Release Technology:	Sentry Soil Protection
Foot Traffic Recommendation TARR:	Severe

SUSTAINABILITY

IAQ Green Label Plus:	CRI Green Label Plus GLP1171
Pre-Consumer Recycled Content:	50%
NSF 140:	EcoFlex NXT - NSF 140 Gold
Declare Label:	Declared Red List Free

PERFORMANCE

Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE

Warranties:	Lifetime Limited Carpet Tile Warranty, Lifetime Duracolor Stain Warranty, Lifetime Static
-------------	---



149
Cool



259
Hip




379
Mod



459
Chic



569
Trendy



579
New Wave



659
Current



939
Instyle