





DESIGN

| | |
|-----------------------------------|---|
| Tufted Pile Weight: | 23.0 oz. per sq. yd. (780 g/m2) |
| Product Type: | Tile |
| Construction: | Tufted |
| Minimum Sq. Yd.: | No Minimum |
| Surface Texture: | Textured Patterned Loop |
| Gauge: | 1/12 (47.00 rows per 10 cm) |
| Density: | 8,038 |
| Weight Density: | 184,893 |
| Stitches Per Inch: | 11.0 (43.31 per 10 cm) |
| Finished Pile Thickness: | .103" (2.62 mm) |
| Dye Method: | Solution Dyed / Yarn Dyed |
| Backing Material: | EcoFlex NXT |
| Fiber Type: | Duracolor® Premium Nylon |
| Fiber Technology: | Duracolor® by Mohawk Group's Stain Resistant System. Passes GSA requirements for permanent stain resistant carpet. |
| Pattern Repeat: | Not Applicable |
| Size: | 24" x 24" (.6096 m x .6096 m) |
| Installation Method: | Quarter Turn, Vertical Ashlar, Brick Ashlar |
| GSA Stain Release Rating: | Pass |
| Stain Release Technology: | Permanent, Built into Fiber |
| Soil Release Technology: | Sentry Soil Protection |
| Foot Traffic Recommendation TARR: | Heavy |



149
Cool



259
Hip



379
Mod




459
Chic



569
Trendy



579
New Wave



659
Current



939
Instyle

SUSTAINABILITY

| | |
|--------------------------------|-------------------------------------|
| IAQ Green Label Plus: | CRI Green Label Plus GLP1171 |
| Pre-Consumer Recycled Content: | 51% |
| NSF 140: | EcoFlex NXT - NSF 140 Gold |
| Declare Label: | Declared Red List Free |

PERFORMANCE

| | |
|----------------|---------------------------------------|
| Static: | AATCC-134 Under 3.5 KV |
| Flammability: | ASTM E 648 Class 1 (Glue Down) |
| Smoke Density: | ASTM E 662 Less than 450 |

SERVICE

| | |
|-------------|--|
| Warranties: | Lifetime Limited Carpet Tile Warranty, Lifetime Duracolor Stain Warranty, Lifetime Static |
|-------------|--|