



DESIGN

Product Type:	Tile
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Patterned Tip Shear
Gauge:	1/12 (47.00 rows per 10 cm)
Density:	6,415
Weight Density:	115,485
Stitches Per Inch:	12.0 (47.24 per 10 cm)
Finished Pile Thickness:	.101" (2.57 mm)
Dye Method:	Solution Dyed
Backing Material:	EcoFlex NXT
Fiber Type:	Duracolor® Premium Nylon
Fiber Technology:	Duracolor® by Mohawk Group's Stain Resistant System. Passes GSA requirements for permanent stain resistant carpet.
Face Weight:	18.0 oz. per sq. yd. (610 g/m2)
Pattern Repeat:	Not Applicable
Size:	24" x 24" (.6096 m x .6096 m)
Installation Method:	QuarterTurn, Monolithic, BrickAshlar, VerticalAshlar, MultiDirectional
Soil Release Technology:	Sentry Soil Protection
Foot Traffic Recommendation TARR:	Heavy

SUSTAINABILITY

IAQ Green Label Plus:	CRI Green Label Plus GLP1171
Pre-Consumer Recycled Content:	57%
Post-Consumer Recycled Content:	1%
NSF 140:	EcoFlex NXT - NSF 140 Gold
Declare Label:	Declared Red List Free

PERFORMANCE

Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE

Warranties:	Lifetime Limited Carpet Tile Warranty, Lifetime Duracolor Stain Warranty, Lifetime Static
-------------	---



989
Metro




969
Dashing




957
Urban



949
Sharp



937
Mod



861
Haste



849
Downtown



837
Posh



728
Uptown



661
Stroll



589
Cool



566
Chic



473
Vogue



263
Flashing



148
Swift