




**DESIGN**

Tufted Pile Weight:	<b>18.0 oz. per sq. yd. (610 g/m2)</b>
Product Type:	<b>Tile</b>
Construction:	<b>Tufted</b>
Minimum Sq. Yd.:	<b>No Minimum</b>
Surface Texture:	<b>Patterned Tip Shear</b>
Gauge:	<b>1/12 (47.00 rows per 10 cm)</b>
Density:	<b>6,416</b>
Weight Density:	<b>115,488</b>
Stitches Per Inch:	<b>11.0 (43.31 per 10 cm)</b>
Finished Pile Thickness:	<b>.101" (2.56 mm)</b>
Dye Method:	<b>Solution Dyed</b>
Backing Material:	<b>EcoFlex NXT</b>
Fiber Type:	<b>Duracolor® Premium Nylon</b>
Fiber Technology:	<b>Duracolor® by Mohawk Group's Stain Resistant System. Passes GSA requirements for permanent stain resistant carpet.</b>
Pattern Repeat:	<b>Not Applicable</b>
Size:	<b>12" x 36" (.3048 m x .9144 m)</b>
Installation Method:	<b>Monolithic, HalfLap, BrickAshlar, BasketWeave, PlankHalfLap, MonolithicStepping, Random, Herringbone</b>
Soil Release Technology:	<b>Sentry Soil Protection</b>
Foot Traffic Recommendation TARR:	<b>Heavy</b>




148  
Classic



263  
Rare



473  
Unique



566  
Distinguished



589  
Superior




661  
Ripe



728  
Finest



837  
Prime



849  
Flawless

**SUSTAINABILITY**

IAQ Green Label Plus:	<b>CRI Green Label Plus GLP1171</b>
Pre-Consumer Recycled Content:	<b>57%</b>
Post-Consumer Recycled Content:	<b>1%</b>
NSF 140:	<b>EcoFlex NXT - NSF 140 Gold</b>
Declare Label:	<b>Declared Red List Free</b>

**PERFORMANCE**

Static:	<b>AATCC-134 Under 3.5 KV</b>
Flammability:	<b>ASTM E 648 Class 1 (Glue Down)</b>
Smoke Density:	<b>ASTM E 662 Less than 450</b>

**SERVICE**


Warranties:	<b>Lifetime Limited Carpet Tile Warranty, Lifetime Duracolor Stain Warranty, Lifetime Static</b>
-------------	--




861  
Tradition



937  
Simple



949  
Ideal



957  
Top Notch



969  
Mature



989  
Masterly