



**DESIGN**

Tufted Pile Weight:	<b>18.0 oz. per sq. yd. (610 g/m2)</b>
Product Type:	<b>Tile</b>
Construction:	<b>Tufted</b>
Minimum Sq. Yd.:	<b>No Minimum</b>
Surface Texture:	<b>Patterned Tip Shear</b>
Gauge:	<b>1/12 (47.00 rows per 10 cm)</b>
Density:	<b>6,416</b>
Weight Density:	<b>115,488</b>
Stitches Per Inch:	<b>11.0 (43.31 per 10 cm)</b>
Finished Pile Thickness:	<b>.101" (2.56 mm)</b>
Dye Method:	<b>Solution Dyed</b>
Backing Material:	<b>EcoFlex NXT</b>
Fiber Type:	<b>Duracolor® Tricor Premium Nylon</b>
Fiber Technology:	<b>Duracolor® by Mohawk Group's Stain Resistant System. Passes GSA requirements for permanent stain resistant carpet.</b>
Pattern Repeat:	<b>Not Applicable</b>
Size:	<b>12" x 36" (.3048 m x .9144 m)</b>
Installation Method:	<b>Monolithic, Half Lap, Brick Ashlar, Basket Weave, Plank Half Lap, Monolithic Stepping, Random, Herringbone</b>
GSA Stain Release Rating:	<b>Pass</b>
Stain Release Technology:	<b>Permanent, Built into Fiber</b>
Soil Release Technology:	<b>Sentry Soil Protection</b>
Foot Traffic Recommendation TARR:	<b>Heavy</b>

**SUSTAINABILITY**

IAQ Green Label Plus:	<b>CRI Green Label Plus GLP1171</b>
Pre-Consumer Recycled Content:	<b>57%</b>
NSF 140:	<b>EcoFlex NXT - NSF 140 Gold</b>
Declare Label:	<b>Declared Red List Free</b>

**PERFORMANCE**

Static:	<b>AATCC-134 Under 3.5 KV</b>
Flammability:	<b>ASTM E 648 Class 1 (Glue Down)</b>
Smoke Density:	<b>ASTM E 662 Less than 450</b>

**SERVICE**

Warranties:	<b>Lifetime Limited Carpet Tile Warranty, Lifetime Duracolor Stain Warranty, Lifetime Static</b>
-------------	--



148  
Classic



263  
Rare



473  
Unique



566  
Distinguished



589  
Superior



661  
Ripe



728  
Finest



837  
Prime




849  
Flawless




861  
Tradition



937  
Simple



949  
Ideal



957  
Top Notch



969  
Mature



989  
Masterly