



DESIGN

Tufted Pile Weight:	24.0 oz. per sq. yd. (814 g/m ²)
Product Type:	Tile
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Textured Patterned Loop
Gauge:	1/12 (47.00 rows per 10 cm)
Density:	8,307
Weight Density:	199,384
Stitches Per Inch:	11.0 (43.31 per 10 cm)
Finished Pile Thickness:	.104" (2.64 mm)
Dye Method:	Yarn Dyed
Backing Material:	EcoFlex NXT
Fiber Type:	Duracolor® Premium Nylon
Fiber Technology:	Duracolor® by Mohawk Group's Stain Resistant System. Passes GSA requirements for permanent stain resistant carpet.
Pattern Repeat:	Not Applicable
Size:	24" x 24" (.6096 m x .6096 m)
Installation Method:	Basket Weave, Herringbone, Quarter Turn, Multi Directional, Vertical Ashlar, Horizontal Ashlar
GSA Stain Release Rating:	Pass
Stain Release Technology:	Permanent, Built into Fiber
Soil Release Technology:	Sentry Soil Protection
Foot Traffic Recommendation TARR:	Severe

SUSTAINABILITY

IAQ Green Label Plus:	CRI Green Label Plus GLP1171
Pre-Consumer Recycled Content:	46%
NSF 140:	EcoFlex NXT - NSF 140 Gold
Declare Label:	Declared Red List Free

PERFORMANCE

Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE

Warranties:	Lifetime Limited Carpet Tile Warranty, Lifetime Duracolor Stain Warranty, Lifetime Static
-------------	---



136
Entertained



263
Enticed



569
Fortunate



589
Tickled



652
Humored



738
Merry



859
Peppy



868
Pleased



879
Chipper



939
Interested



949
Buoyant



959
Refreshed



968
Comical



988
Excited



989
Overjoyed