



DESIGN

| | |
|-----------------------------------|--|
| Product Type: | Tile |
| Construction: | Tufted |
| Minimum Sq. Yd.: | No Minimum |
| Surface Texture: | Textured Patterned Loop |
| Gauge: | 1/12 (47.00 rows per 10 cm) |
| Density: | 7,826 |
| Weight Density: | 156,521 |
| Stitches Per Inch: | 10.5 (41.34 per 10 cm) |
| Finished Pile Thickness: | .092" (2.34 mm) |
| Dye Method: | Solution Dyed / Yarn Dyed |
| Backing Material: | EcoFlex NXT |
| Fiber Type: | Duracolor® Premium Nylon |
| Fiber Technology: | Duracolor® by Mohawk Group's Stain Resistant System. Passes GSA requirements for permanent stain resistant carpet. |
| Face Weight: | 20.0 oz. per sq. yd. (678 g/m ²) |
| Pattern Repeat: | Not Applicable |
| Size: | 24" x 24" (.6096 m x .6096 m) |
| Installation Method: | QuarterTurn, VerticalAshlar, BrickAshlar |
| Soil Release Technology: | Sentry Soil Protection |
| Foot Traffic Recommendation TARR: | Severe |

SUSTAINABILITY


| | |
|---------------------------------|------------------------|
| IAQ Green Label Plus: | Green Label Plus 1171 |
| Pre-Consumer Recycled Content: | 56% |
| Post-Consumer Recycled Content: | 1% |
| NSF 140: | Gold |
| Declare Label: | Declared Red List Free |

PERFORMANCE

| | |
|----------------|--------------------------------|
| Static: | AATCC-134 Under 3.5 KV |
| Flammability: | ASTM E 648 Class 1 (Glue Down) |
| Smoke Density: | ASTM E 662 Less than 450 |

SERVICE

| | |
|-------------|---|
| Warranties: | Lifetime Limited Carpet Tile Warranty, Lifetime Duracolor Stain Warranty, Lifetime Static |
|-------------|---|



138 Pulse



576 Ripple



665 Billow



739 Blast



856 Tide



883 Undulate



949 Cadence



955 Flow



956 Rhythm



978
Burst