



DESIGN

| | |
|-----------------------------------|---|
| Tufted Pile Weight: | 18.0 oz. per sq. yd. (610 g/m2) |
| Product Type: | Tile |
| Construction: | Tufted |
| Minimum Sq. Yd.: | No Minimum |
| Surface Texture: | Textured Patterned Loop |
| Gauge: | 1/12 (47.00 rows per 10 cm) |
| Density: | 8,100 |
| Weight Density: | 145,800 |
| Stitches Per Inch: | 11.0 (43.31 per 10 cm) |
| Finished Pile Thickness: | .080" (2.03 mm) |
| Dye Method: | Solution Dyed |
| Backing Material: | EcoFlex NXT |
| Fiber Type: | Duracolor® Premium Nylon |
| Fiber Technology: | Duracolor® by Mohawk Group's Stain Resistant System. Passes GSA requirements for permanent stain resistant carpet. |
| Pattern Repeat: | Not Applicable |
| Size: | 24" x 24" (.6096 m x .6096 m) |
| Installation Method: | Monolithic, QuarterTurn, BrickAshlar, VerticalAshlar, MultiDirectional |
| Soil Release Technology: | Sentry Soil Protection |
| Foot Traffic Recommendation TARR: | Severe |

SUSTAINABILITY

| | |
|---------------------------------|-------------------------------------|
| IAQ Green Label Plus: | CRI Green Label Plus GLP1171 |
| Pre-Consumer Recycled Content: | 57% |
| Post-Consumer Recycled Content: | 1% |
| NSF 140: | EcoFlex NXT - NSF 140 Gold |
| Declare Label: | Declared Red List Free |

PERFORMANCE

| | |
|----------------|---------------------------------------|
| Static: | AATCC-134 Under 3.5 KV |
| Flammability: | ASTM E 648 Class 1 (Glue Down) |
| Smoke Density: | ASTM E 662 Less than 450 |

SERVICE

| | |
|-------------|--|
| Warranties: | Lifetime Limited Carpet Tile Warranty, Lifetime Duracolor Stain Warranty, Lifetime Static |
|-------------|--|



263
Cayenne
Quickship Available



566
Peacock
Quickship Available



589
Magic
Quickship Available



661
Greenery
Quickship Available



849
Hound
Quickship Available



861
Subtle
Quickship Available



949
Everglade
Quickship Available



957
Metro
Quickship Available



969
Cocoa
Quickship Available



989
Mystic
Quickship Available