



DESIGN

Tufted Pile Weight:	19.0 oz. per sq. yd. (644 g/m2)
Product Type:	Tile
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Textured Patterned Loop
Gauge:	1/12 (47.00 rows per 10 cm)
Density:	7,685
Weight Density:	146,015
Stitches Per Inch:	10.8 (42.52 per 10 cm)
Finished Pile Thickness:	.089" (2.26 mm)
Dye Method:	Solution Dyed
Backing Material:	EcoFlex ICT
Fiber Type:	Antron® Lumena™ Nylon
Pattern Repeat:	Not Applicable
Size:	12" x 36" (.3048 m x .9144 m)
Installation Method:	Half Lap, Brick Ashlar, Basket Weave, Plank Half Lap, Random, Herringbone
Soil Release Technology:	DuraTech®
Foot Traffic Recommendation TARR:	Severe

SUSTAINABILITY

IAQ Green Label Plus:	CRI Green Label Plus GLP1098
Pre-Consumer Recycled Content:	41%
NSF 140:	EcoFlex ICT - NSF 140 Gold
Declare Label:	Declared Red List Free

PERFORMANCE

Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE

Warranties:	Lifetime Limited Carpet Tile Warranty, Lifetime Static
-------------	---



727
Transform



739
Convert



847
Reshape



859
Adjust



868
Fixed



947
Complex



969
Reform



979
Modify



988
Adapt