



**DESIGN**

---

Tufted Pile Weight:	<b>26.0 oz. per sq. yd. (882 g/m<sup>2</sup>)</b>
Product Type:	<b>Broadloom-Custom</b>
Construction:	<b>Tufted</b>
Minimum Sq. Yd.:	<b>500 sq yd minimum</b>
Surface Texture:	<b>Textured Patterned Cut and Loop</b>
Gauge:	<b>1/12 (47.00 rows per 10 cm)</b>
Density:	<b>5,474</b>
Weight Density:	<b>142,324</b>
Stitches Per Inch:	<b>12.3 (48.43 per 10 cm)</b>
Finished Pile Thickness:	<b>.171" (4.34 mm)</b>
Dye Method:	<b>Solution Dyed / Yarn Dyed</b>
Backing Material:	<b>Unibond® Plus</b>
Fiber Type:	<b>Duracolor® Premium Nylon</b>
Fiber Technology:	<b>Duracolor® by Mohawk Group's Stain Resistant System. Passes GSA requirements for permanent stain resistant carpet.</b>
Pattern Repeat:	<b>18" (W) x 17.5" (L)</b>
Width:	<b>12' width (3.66 m)</b>
Soil Release Technology:	<b>Sentry Soil Protection</b>
Foot Traffic Recommendation TARR:	<b>Heavy</b>

**SUSTAINABILITY**

---

IAQ Green Label Plus:	<b>CRI Green Label Plus GLP3802</b>
Pre-Consumer Recycled Content:	<b>34%</b>
Post-Consumer Recycled Content:	<b>2%</b>
NSF 140:	<b>Unibond Plus - NSF 140 Gold</b>
Declare Label:	<b>Declared Red List Free</b>

**PERFORMANCE**

---

Static:	<b>AATCC-134 Under 3.5 KV</b>
Flammability:	<b>ASTM E 648 Class 1 (Glue Down)</b>
Smoke Density:	<b>ASTM E 662 Less than 450</b>

**SERVICE**

---

Warranties:	<b>Lifetime Limited Unibond® Plus Warranty, Lifetime Duracolor Stain Warranty, Lifetime Static</b>
-------------	--




152  
Artifacts



368  
Market



483  
Trails



558  
Woodcraft




568  
Cultural




646  
Caravan



648  
Trade



651  
Transcontinental



668  
Connection



721  
Route



849  
Influence



852  
Exchange



856  
Technique