



DESIGN

| | |
|-----------------------------------|---|
| Product Type: | Broadloom-Custom |
| Construction: | Tufted |
| Minimum Sq. Yd.: | 500 sq yd minimum |
| Surface Texture: | Textured Patterned Cut and Loop |
| Gauge: | 1/12 (47.00 rows per 10 cm) |
| Density: | 5,474 |
| Weight Density: | 142,324 |
| Stitches Per Inch: | 12.3 (48.43 per 10 cm) |
| Finished Pile Thickness: | .171" (4.34 mm) |
| Dye Method: | Solution Dyed / Yarn Dyed |
| Backing Material: | Unibond® Plus |
| Fiber Type: | Duracolor® Premium Nylon |
| Fiber Technology: | Duracolor® by Mohawk Group's Stain Resistant System. Passes GSA requirements for permanent stain resistant carpet. |
| Face Weight: | 26.0 oz. per sq. yd. (882 g/m2) |
| Pattern Repeat: | 18" (W) x 46" (L) |
| Width: | 12' width (3.66 m) |
| Soil Release Technology: | Sentry Soil Protection |
| Foot Traffic Recommendation TARR: | Heavy |

SUSTAINABILITY

| | |
|---------------------------------|-------------------------------|
| IAQ Green Label Plus: | Green Label Plus 3802 |
| Pre-Consumer Recycled Content: | 34% |
| Post-Consumer Recycled Content: | 2% |
| NSF 140: | Gold |
| Declare Label: | Declared Red List Free |

PERFORMANCE

| | |
|----------------|---------------------------------------|
| Static: | AATCC-134 Under 3.5 KV |
| Flammability: | ASTM E 648 Class 1 (Glue Down) |
| Smoke Density: | ASTM E 662 Less than 450 |

SERVICE

| | |
|-------------|--|
| Warranties: | Lifetime Limited Unibond® Plus Warranty, Lifetime Duracolor Stain Warranty, Lifetime Static |
|-------------|--|




152
Artifacts



368
Market




483
Trails



558
Woodcraft



568
Cultural




646
Caravan



648
Trade



651
Transcontinental



668
Connection



721
Route



852
Exchange



849
Influence



856
Technique