



## DESIGN

|                                   |   |
|-----------------------------------|---|
| Product Type:                     | <b>Broadloom-Custom</b>   |
| Construction:                     | <b>Tufted</b>   |
| Minimum Sq. Yd.:                  | <b>500 sq yd minimum</b>  |
| Surface Texture:                  | <b>Textured Patterned Cut and Loop</b>  |
| Gauge:                            | <b>1/12 (47.00 rows per 10 cm)</b>  |
| Density:                          | <b>5,474</b>  |
| Weight Density:                   | <b>142,324</b>  |
| Stitches Per Inch:                | <b>12.3 (48.43 per 10 cm)</b>   |
| Finished Pile Thickness:          | <b>.171" (4.34 mm)</b>  |
| Dye Method:                       | <b>Solution Dyed / Yarn Dyed</b>  |
| Backing Material:                 | <b>Unibond® Plus</b>  |
| Fiber Type:                       | <b>Duracolor® Premium Nylon</b>   |
| Fiber Technology:                 | <b>Duracolor® by Mohawk Group's Stain Resistant System. Passes GSA requirements for permanent stain resistant carpet.</b> |
| Face Weight:                      | <b>26.0 oz. per sq. yd. (882 g/m2)</b>  |
| Pattern Repeat:                   | <b>18" (W) x 24" (L)</b>  |
| Width:                            | <b>12' width (3.66 m)</b>   |
| Soil Release Technology:          | <b>Sentry Soil Protection</b>   |
| Foot Traffic Recommendation TARR: | <b>Heavy</b>  |

## SUSTAINABILITY

|                                 |                               |
|---------------------------------|-------------------------------|
| IAQ Green Label Plus:           | <b>Green Label Plus 3802</b>  |
| Pre-Consumer Recycled Content:  | <b>34%</b>                    |
| Post-Consumer Recycled Content: | <b>2%</b>                     |
| NSF 140:                        | <b>Gold</b>                   |
| Declare Label:                  | <b>Declared Red List Free</b> |

## PERFORMANCE

|                |                                       |
|----------------|---------------------------------------|
| Static:        | <b>AATCC-134 Under 3.5 KV</b>         |
| Flammability:  | <b>ASTM E 648 Class 1 (Glue Down)</b> |
| Smoke Density: | <b>ASTM E 662 Less than 450</b>       |

## SERVICE

|             |  |
|-------------|--|
| Warranties: | <b>Lifetime Limited Unibond® Plus Warranty, Lifetime Duracolor Stain Warranty, Lifetime Static</b> |
|-------------|--|



152  
Artifacts



368  
Market



483  
Trails



558  
Woodcraft



568  
Cultural



646  
Caravan



648  
Trade



651  
Transcontinental



668  
Connection



721  
Route



852  
Exchange



849  
Influence



856  
Technique